

General information

Table of Contents

General information	1
Usage of modules	2
Information on new software stack and lmod	2
List of available modules	4
Machine Learning Software	4
Using the old stack	4
Compilers (relevant for legacy stack only!)	5
Profiling and analysis tools (relevant for legacy stack only!)	5
MPI programs	5

Usage of modules

Based on the requirements by the DEEP-EST applications several software tools have already been installed on the DEEP system/DEEP-ER SDV. To see which modules are available use

```
module avail
```

For most tools and compilers there are several versions available, you can list the different versions of a specific tool with `module avail ?tool name?`, for example

```
-bash-4.1$ module avail intel

----- /usr/local/modulefiles/COMPILER -----
intel/13.0.4      intel/15.0      intel/16.0      intel/16.3      intel/17.1      intel/18.0
intel/14.0.3      intel/15.2.164  intel/16.2(default)  intel/17.0      intel/17.2      intel/18.1
```

You can load a specific version or just use the default with for example

```
module load intel
```

The modules which are currently loaded can be listed with the command `?module list?`. To unload a module just type `?module unload?` followed by the name of the module.

Information on new software stack and lmod

Since the second half of 2018 a new software stack managed via Easybuild is available on the system (more information on Easybuild is available [here](#)).

The software made available on the new stack via Easybuild is arranged hierarchically, with only some core modules made available to the user at login. Typically, these core modules include the compilers, or some other standalone tools (i.e. JUBE). Loading such core modules via `module load` allows the list of available modules to increase, including the modules that are installed with the fore-mentioned core module as a dependency.

A typical workflow would be the following. After logging in, the user would be in this situation (note: the examples below were produced with the old Haswell stack):

```
$ module avail

----- /usr/local/software/haswell/Stages/2018a/modules/all/Compiler/mpi/
Autotools/20170619  CMake/3.9.6      CMake/3.11.1      Doxygen/1.8.14    LLVM/5.0.1      Perl/5.26.1      Python/2.7.
Bazel/0.11.1       CMake/3.10.3     CMake/3.12.2 (D)   GMP/6.1.2         PAPI/5.6.0      PostgreSQL/10.3  Python/3.6.
----- /usr/local/software/haswell/Stages/2018a/UI/Com
Intel/2018.2.199-GCC-5.5.0

----- /usr/local/software/haswell/Stages/2018a/UI/T
Advisor/2018_update3  EasyBuild/3.6.1  JUBE/2.2.1      Java/1.8.0_162    VTune/2018_update3  intel-para/2018a-mt

Where:
D: Default Module
```

Loading the Intel compiler (Intel/2018.2.199-GCC-5.5.0 module), allows the list of available tools to be expanded:

```
module load Intel/2018.2.199-GCC-5.5.0
module avail

----- /usr/local/software/haswell/Stages/2018a/modules/all/Compiler/mpi/
ParaStationMPI/5.2.1-1-mt  ParaStationMPI/5.2.1-1 (D)
----- /usr/local/software/haswell/Stages/2018a/modules/all/Compiler/in
mkl-dnn/0.13
```

```

----- /usr/local/software/haswell/Stages/2018a/modules/all/Compil
Autotools/20170619    CMake/3.9.6    CMake/3.11.1    Doxygen/1.8.14    LLVM/5.0.1    Perl/5.26.1    Python/2.7.
Bazel/0.11.1        CMake/3.10.3    CMake/3.12.2 (D)    GMP/6.1.2        PAPI/5.6.0    PostgreSQL/10.3    Python/3.6.
----- /usr/local/software/haswell/Stages/2018a/UI/Com
Intel/2018.2.199-GCC-5.5.0 (L)
----- /usr/local/software/haswell/Stages/2018a/UI/T
Advisor/2018_update3    EasyBuild/3.6.1    JUBE/2.2.1    Java/1.8.0_162    VTune/2018_update3    intel-para/2018a-mt

Where:
L:  Module is loaded
D:  Default Module

```

After further loading an MPI library, the user can then access all parallel tools that require MPI:

```

module load ParaStationMPI/5.2.1-1
module avail

----- /usr/local/software/haswell/Stages/2018a/modules/all/MPI/intel/2018.2
Boost/1.66.0-Python-2.7.14    Extrae/3.5.2    FTI/1.2    HDF5/1.8.20    PETSc/3.9.0_int8    R/3.4.3
Boost/1.66.0-Python-3.6.5 (D)    FFTW/3.3.7    GSL/2.4    PETSc/3.9.0_complex    PETSc/3.9.0 (D)    SIONlib/1.7.
----- /usr/local/software/haswell/Stages/2018a/modules/all/Compiler/mpi/
ParaStationMPI/5.2.1-1-mt    ParaStationMPI/5.2.1-1 (L,D)
----- /usr/local/software/haswell/Stages/2018a/modules/all/Compiler/in
mkl-dnn/0.13
----- /usr/local/software/haswell/Stages/2018a/modules/all/Compil
Autotools/20170619    CMake/3.9.6    CMake/3.11.1    Doxygen/1.8.14    LLVM/5.0.1    Perl/5.26.1    Python/2.7.
Bazel/0.11.1        CMake/3.10.3    CMake/3.12.2 (D)    GMP/6.1.2        PAPI/5.6.0    PostgreSQL/10.3    Python/3.6.
----- /usr/local/software/haswell/Stages/2018a/UI/Com
Intel/2018.2.199-GCC-5.5.0 (L)
----- /usr/local/software/haswell/Stages/2018a/UI/T
Advisor/2018_update3    EasyBuild/3.6.1    JUBE/2.2.1    Java/1.8.0_162    VTune/2018_update3    intel-para/2018a-mt

Where:
L:  Module is loaded
D:  Default Module

```

It can be seen from the previous examples that with the new software stack, the command `module avail` does not allow the user to visualize all the modules actually installed on the system, but rather the ones made available by the system with the modules previously loaded up to that point. In order to explore the full hierarchy of modules, the command

`module spider`

must be used. After enabling the new stack on a new shell, it's possible to search for a certain module (Extrae, for instance) with the following instructions:

```

$ ml spider Extrae

-----
Extrae: Extrae/3.5.2
-----

Description:
  Extrae is the core instrumentation package developed by the Performance Tools group at BSC. Extrae is capable of inst

```

StarSs1 using different instrumentation approaches. The information gathered by Extrae typically includes timestamped events of runtime calls, performance counters and source code references. Besides, Extrae provides its own API to allow the user to manually instrument his or her application.

You will need to load all module(s) on any one of the lines below before the "Extrae/3.5.2" module is available to load.

```
Intel/2018.2.199-GCC-5.5.0 ParaStationMPI/5.2.1-1
```

Help:

Description

=====

Extrae is the core instrumentation package developed by the Performance Tools group at BSC. Extrae is capable of instrumenting applications based on MPI, OpenMP, pthreads, CUDA1, OpenCL1, and StarSs1 using different instrumentation approaches. The information gathered by Extrae typically includes timestamped events of runtime calls, performance counters and source code references. Besides, Extrae provides its own API to allow the user to manually instrument his or her application.

More information

=====

- Homepage: <http://www.bsc.es/computer-sciences/performance-tools>
- Site contact: sc@fz-juelich.de

The description provided by the module spider command includes also a list of modules that need to be loaded, in order to be able to load the Extrae module.

The module spider command is part of a new implementation of the old module command, namely lmod. Together with this added functionality, lmod provides also a wrapper around the module command: the ml command. This wrapper has some user-friendly features:

- ml alone lists all the currently loaded modules;
- ml +module (or ml module) allows to load a specific module (e.g. ml Intel loads the default version of the Intel module);
- ml -module unloads the previously loaded module (e.g. ml -Intel removes the currently loaded version of the Intel module);
- the ml wrapper can be used instead of module for all the subcommands of module (e.g. ml avail or ml av, or ml restore, etc.)

More information on lmod can be found [?here](#).

List of available modules

A list of the modules currently available on the Easybuild stack of the DEEP System can be found [?here](#).

Machine Learning Software

In preparation for the deployment of the cluster module, a new software stack compiled for Skylake is being installed on the system. Machine Learning software is available on this stack. This Skylake stack can be enabled with the following commands:

```
ml purge
ml unuse $MODULEPATH
ml use /usr/local/software/skylake/Stages/2018b/UI/Tools/
ml use /usr/local/software/skylake/Stages/2018b/UI/Compilers/
ml Intel
```

This stack is also managed with Easybuild and is hierarchically structured.

This stack is currently under development: please use ml spider after enabling this stack to check the status of the software installed on it.

Using the old stack

As of July 2019, a new software stack compiled for Skylake is loaded by default on the DEEP-EST system.

The old Haswell stack (necessary to use the deeper-sdv nodes) can be enabled with the command:

```
enable_old_stack
```

If the old stack is needed in a batch script, the alias given above does not work. To circumvent this issue, please add the following lines to your script before calling the `enable_old_stack` command:

```
shopt -s expand_aliases
. /usr/local/software/configs/modules.sh
```

The very old stack installed before the transition to Easybuild is still available on the system with the command:

```
enable_legacy_stack
```

As with the old Easybuild stack, the lines reported above must be included in your batch script to run the `enable_legacy_stack` command in a batch job.

Compilers (relevant for legacy stack only!)

There are several compilers available, but as it is highly recommended to use the Intel compiler on the KNC system it might be best to also use it on the DEEP system.

Installed compilers:

- Intel compiler: `module load intel`
- GNU compiler: `module load gcc`
- PGI Compiler: `module load pgc`

Profiling and analysis tools (relevant for legacy stack only!)

- Intel VTune: `module load VTune`
- Intel Advisor: `module load Advisor`
- Intel Inspector: `module load Inspector`
- ScoreP: `module load scorep`
- Darshan: `module load darshan`
- Extrae: `module load UNITE extrae`
- Scalasca: `module load UNITE scalasca`

MPI programs

It is recommended to use the ParaStation MPI installation.