

Overview of our systems

This page is supposed to give a short overview on the available systems from a hardware point of view. All hardware can be reached through a login node via SSH: **deep@fz-juelich.de**. The login node is implemented as virtual machine hosted by the master nodes (in a failover mode). Please, see also information about [getting an account](#) and using the [batch system](#).

Rack plan

This is a sketch of the available hardware including a short description of the hardware interesting for the system users (the nodes you can use for running your jobs and that can be used for testing).

SSSM rack

This rack hosts the master nodes, files servers and the storage as well as network components for the Gigabit Ethernet administration and service networks. Users can access the login node via **deep@fz-juelich.de** (implemented as virtual machine running on the master nodes).

CM rack

Contains the hardware of the DEEP-EST Cluster Module including compute nodes, management nodes, network components and liquid cooling unit.

Cluster [50 nodes]: `dp-cn[01-50]`

- 2 Intel Xeon 'Skylake' Gold 6146 (12 cores (24 threads), 3.2GHz)
- 192 GB RAM
- 1 x 400GB NVMe SSD (for OS only, not exposed to users)
- network: IB EDR (100 Gb/s)

DAM rack

This rack hosts the nodes of the Data Analytics Module of the DEEP-EST prototype. Currently it contains four test servers:

Data Analytics Module [16 nodes]: `dp-dam[01-16]`

- 2 x Intel Xeon 'Cascade Lake' Platinum 8260M CPU @ 2.40GHz
- 1 x Nvidia V100 Tesla GPU (32 GB HBM2)
- 1 x Intel STRATIX10 FPGA (32 GB DDR4)
- 384 GB RAM + 2 or 3 TB non-volatile memory (14 nodes with 2, 2 nodes with 3)
- 2 x 1.5 TB Intel Optane SSD
- 1 x 240 GB SSD (for boot and OS)
- network: EXTOLL + 40 Gb Ethernet

SDV rack

Along with the prototype systems several test nodes and so called software development vehicles have been installed in the scope of the DEEP(-ER,EST) projects. These are located in the SDV rack. The following components can be accessed by the users:

Prototype DAM [4 nodes]: `protodam[01-04]`

- 2 x Intel Xeon 'Skylake' (26 cores per socket)
- 192 GB RAM
- network: Gigabit Ethernet

Cluster [16 nodes]: `deeper-sdv[01-16]`

- 2 Intel Xeon 'Haswell' E5-v2680 v3 (2.5 GHz)
- 128 GB RAM
- 1 NVMe with 400 GB per node(accessible through BeeGFS on demand)
- network: 100 Gb/s Extoll tourmalet

KNLs [4 nodes]: `kn1[01,04-06]`

- 1 Intel Xeon Phi (64-68 cores)
- 1 NVMe with 400 GB per node (accessible through BeeGFS on demand)
- 16 GB MCDRAM plus 96 GB RAM per KNL
- network: Gigabit Ethernet

GPU nodes for ML [3 nodes]: `m1-gpu[01-03]`

- 2 x Intel Xeon 'Skylake' Silver 4112 (2.6 GHz)
- 192 GB RAM
- 4 x Nvidia Tesla V100 GPU (PCIe Gen3), 16 GB HBM2
- network: 40GbE connection
- NAM:
 - size: 2 GB
 - network: Extoll
 - details: [?https://www.deep-projects.eu/hardware/memory-hierarchies/49-nam](https://www.deep-projects.eu/hardware/memory-hierarchies/49-nam)

Network overview

Different types of interconnects are in use along with the Gigabit Ethernet connectivity (used for administration and service network) that is available for all the nodes. The following sketch should give a rough overview. Network details will be of particular interest for the storage access. Please also refer to the description of the [filesystems](#).

Further information

- [Information about the batchsystem](#)
- [Filesystems](#)
- [Information on available software and tools](#)
- [Use the DEEP-EST Cluster Module](#)
- [Use the SDV Cluster](#)
- [Use the SDV KNLs](#)